

DATA SHEET FOR THREE-PHASE SQUIRREL-CAGE MOTOR

Type: DM3 315M4

Electrical data			
Rated motor frequency	50Hz	60Hz	
Rated motor power	132,0	158,4	kW
Rated motor speed	1490	1788	RPM
Rated motor voltage	400 / 690	440 - 480	V
Rated motor torque	846		Nm
Rated motor current	225,8 / 130,9	246,4 - 225,8	A
Starting motor current	7,0		xIn
Starting motor torque	2,2		xMn
Brakedown motor torque	2,2		
Starting			D.O.L
Efficiency class			
Efficiency	94,80%		100% load
	94,70%		75% load
	93,90%		50% load
Power factor cosp	0,89		100% load

General data		
Frame size	315	mm
Mounting	B3,B5,B35	
Weight	892kg	
Casing material	Cast Iron	
Protection	IP	55
Insulation class	F	
Temp. Rise	80K	
Vibration	2,8mm/s	
Duty	S1	
Dir. Rotation	Both	
PTC	3 x 150°C	
RAL	7031	
Site Conditions		
Ambient temperature	from -20°C to +40°C	
Altitude above sea level	1000 m	

Mechanical data				
Noise level	93	dB(A)	Bearing DE side	6319 C3
Moment of inertia	2,9111	kg/m ²	Bearing NDE side	6319 C3

Certification:
CE

Extras:		
Drawing made by	Date	sign.
Dennis Barrit	26-10-2020	

There may be differences between rating plate and calculated values