DATA SHEET FOR THREE-PHASE SQUIRREL-CAGE MOTOR

Type: DM3 315L4

Electrical data

Rated motor frequency	50Hz	60Hz	
Rated motor power	160,0	192,0	kW
Rated motor speed	1490	1788	RPM
Rated motor voltage	400 / 690	440 - 480	V
Rated motor torque	1026		Nm
Rated motor current	273,4 / 158,5	298,3 - 273,4	A
Starting motor current	7,1		xIn
Starting motor torque	2,0		xMn
Brakedown motor torque	2,2		
Starting			D.O.L
Efficiency class			
Efficiency	94,90%		100% load
	94,90%		75% load
	94,20%		50% load
Power factor cosφ	0,89		100% load

General data

Frame size	315	mm
Mounting	B3,B5,B35	
Weight	973kg	
Casing material	Cast Iron	
Protection	IP	55
Insulation class	F	
Temp. Rise	80K	
Vibration	2,8mm/s	
Duty	S1	
Dir. Rotation	Both	
PTC	3 x 150°C	
RAL	7031	
Site Conditions		
Ambient temperature	from -20°C to +40°C	
Altitude above sea level	1000 m	

Mechanical data

Noise level	97	dB(A)	Bearing DE side	6319 C3
Moment of inertia	3,5829	kg/m2	Bearing NDE side	6319 C3

Certification:

CE

Extras:

Drawing made by	Date	sign.
Dennis Barrit	26-10-2020	

There may be differences between rating plate and calculated values

DM Motors A/S - Hopballevej 60 - 7100 Vejle - Denmark
Phone +45 70 27 13 10 - Fax +45 70 27 13 19 - www.dmmotors.dk