

DATA SHEET FOR THREE-PHASE SQUIRREL-CAGE MOTOR

Type: DM3 180L4

Electrical data			
Rated motor frequency	50Hz	60Hz	
Rated motor power	22,0	26,4	kW
Rated motor speed	1475	1770	RPM
Rated motor voltage	400 / 690	440 - 480	V
Rated motor torque	142		Nm
Rated motor current	40,8 / 23,7	44,5 - 40,8	A
Starting motor current	7,8		xIn
Starting motor torque	2,0		xMn
Brakedown motor torque	2,3		
Starting			D.O.L
Efficiency class			
Efficiency	90,50%		100% load
	90,60%		75% load
	89,90%		50% load
Power factor cosφ	0,86		100% load

General data		
Frame size	180	mm
Mounting	B3,B5,B35	
Weight	178kg	
Casing material	Cast Iron	
Protection	IP	55
Insulation class	F	
Temp. Rise	80K	
Vibration	2,8mm/s	
Duty	S1	
Dir. Rotation	Both	
PTC	3 x 150°C	
RAL	7031	
Site Conditions		
Ambient temperature	from -20°C to +40°C	
Altitude above sea level	1000 m	

Mechanical data				
Noise level	76	dB(A)	Bearing DE side	6311 ZZ C3
Moment of inertia	0,1642	kg/m ²	Bearing NDE side	6311 ZZ C3

Certification:
CE

Extras:		
Drawing made by	Date	sign.
Dennis Barrit	26-10-2020	

There may be differences between rating plate and calculated values