


DATA SHEET FOR THREE-PHASE SQUIRREL-CAGE MOTOR

Type: DM3 132SX2

| Electrical data | | | | General data | | |
|------------------------|--------------|---------------|-----------|--------------------------|---------------------|----|
| Rated motor frequency | 50Hz | 60Hz | | Frame size | 132 | mm |
| Rated motor power | 7,5 | 9,0 | kW | Mounting | B3,B5,B35 | |
| Rated motor speed | 2900 | 3480 | RPM | Weight | 60kg | |
| Rated motor voltage | 400 / 690 | 440 - 480 | V | Casing material | Cast Iron | |
| Rated motor torque | 25 | | Nm | Protection | IP | 55 |
| Rated motor current | 13,98 / 8,11 | 15,25 - 13,98 | A | Insulation class | F | |
| Starting motor current | 7,8 | | xIn | Temp. Rise | 80K | |
| Starting motor torque | 2,2 | | xMn | Vibration | 2,8mm/s | |
| Brakedown motor torque | 2,3 | | | Duty | S1 | |
| Starting | | | D.O.L | Dir. Rotation | Both | |
| Efficiency class | | | | PTC | 3 x 150°C | |
| Efficiency | 87,00% | | 100% load | RAL | 7031 | |
| | 87,70% | | 75% load | Site Conditions | | |
| | 87,30% | | 50% load | Ambient temperature | from -20°C to +40°C | |
| Power factor cosp | 0,89 | | 100% load | Altitude above sea level | 1000 m | |

| Mechanical data | | | | | |
|-------------------|--------|-------------------|------------------|------------|--|
| Noise level | 80 | dB(A) | Bearing DE side | 6308 ZZ C3 | |
| Moment of inertia | 0,0122 | kg/m ² | Bearing NDE side | 6308 ZZ C3 | |

| Certification: | Extras: | | | |
|---|---------|--|-------------|--------------|
|  | | | | |
| | | | | |
| | | | | |
| Drawing made by | | | Date | sign. |
| Dennis Barrit | | | 26-10-2020 | |
| | | | | |

There may be differences between rating plate and calculated values