

DATA SHEET FOR THREE-PHASE SQUIRREL-CAGE MOTOR

Type: DM3 280M4

Electrical data			
Rated motor frequency	50Hz	60Hz	
Rated motor power	90,0	108,0	kW
Rated motor speed	1485	1782	RPM
Rated motor voltage	400 / 690	440 - 480	V
Rated motor torque	579		Nm
Rated motor current	157,2 / 91,1	171,5 - 157,2	A
Starting motor current	6,9		xIn
Starting motor torque	2,2		xMn
Brakedown motor torque	2,3		
Starting			D.O.L
Efficiency class			
Efficiency	93,90%		100% load
	93,70%		75% load
	92,80%		50% load
Power factor cosp	0,88		100% load

General data		
Frame size	280	mm
Mounting	B3,B5,B35	
Weight	556kg	
Casing material	Cast Iron	
Protection	IP	55
Insulation class	F	
Temp. Rise	80K	
Vibration	2,8mm/s	
Duty	S1	
Dir. Rotation	Both	
PTC	3 x 150°C	
RAL	7031	
Site Conditions		
Ambient temperature	from -20°C to +40°C	
Altitude above sea level	1000 m	

Mechanical data			
Noise level	86	dB(A)	
Moment of inertia	1,39	kg/m ²	
Bearing DE side	6317 C3		
Bearing NDE side	6317 C3		

Certification:
CE

Extras:		
Drawing made by	Date	sign.
Dennis Barrit	26-10-2020	

There may be differences between rating plate and calculated values