

# IE3

"Premium Efficiency"



## DATA SHEET FOR THREE-PHASE SQUIRREL-CAGE MOTOR

### Type: DM3-IE3 315L4

Electrical data			
Rated motor frequency	50Hz	60Hz	
Rated motor power	160,0	192,0	kW
Rated motor speed	1490	1788	RPM
Rated motor voltage	400 / 690	440 - 480	V
Rated motor torque	1026		Nm
Rated motor current	270,9 / 157,0	295,5 - 270,9	A
Starting motor current	7,1		xIn
Starting motor torque	2,0		xMn
Brakedown motor torque	2,5		
Starting			D.O.L
Efficiency class	IE3		
Efficiency	95,80%		100% load
	95,90%		75% load
	95,50%		50% load
Power factor cosp	0,89		100% load

General data		
Frame size	315	mm
Mounting	B3,B5,B35	
Weight	1073kg	
Casing material	Cast Iron	
Protection	IP	55
Insulation class	F	
Temp. Rise	80K	
Vibration	2,8mm/s	
Duty	S1	
Dir. Rotation	Both	
PTC	3 x 150°C	
RAL	7031	
Site Conditions		
Ambient temperature	from -20°C to +40°C	
Altitude above sea level	1000 m	

Mechanical data				
Noise level	88	dB(A)	Bearing DE side	6319 C3
Moment of inertia	3,423	kg/m2	Bearing NDE side	6319 C3

**Certification:**

**Extras:**

Drawing made by	Date	sign.
Dennis Barrit	26-10-2020	

There may be differences between rating plate and calculated values