

IE2

"High Efficiency"



DATA SHEET FOR THREE-PHASE SQUIRREL-CAGE MOTOR

Type: DM3-IE2 180M4

Electrical data			
Rated motor frequency	50Hz	60Hz	
Rated motor power	18,5	22,2	kW
Rated motor speed	1475	1770	RPM
Rated motor voltage	400 / 690	440 - 480	V
Rated motor torque	120		Nm
Rated motor current	34,0 / 19,7	37,1 - 34,0	A
Starting motor current	7,8		xIn
Starting motor torque	2,0		xMn
Brakedown motor torque	2,3		
Starting			D.O.L
Efficiency class	IE2		
Efficiency	91,20%		100% load
	91,40%		75% load
	90,70%		50% load
Power factor cosp	0,86		100% load

General data		
Frame size	180	mm
Mounting	B3,B5,B35	
Weight	163kg	
Casing material	Cast Iron	
Protection	IP	55
Insulation class	F	
Temp. Rise	80K	
Vibration	2,8mm/s	
Duty	S1	
Dir. Rotation	Both	
PTC	3 x 150°C	
RAL	7031	
Site Conditions		
Ambient temperature	from -20°C to +40°C	
Altitude above sea level	1000 m	

Mechanical data				
Noise level	75	dB(A)	Bearing DE side	6311 ZZ C3
Moment of inertia	0,146	kg/m2	Bearing NDE side	6311 ZZ C3

Certification:

Extras:

Drawing made by	Date	sign.
Dennis Barrit	26-10-2020	

There may be differences between rating plate and calculated values