

IE3

"Premium Efficiency"



DATA SHEET FOR THREE-PHASE SQUIRREL-CAGE MOTOR

Type: DM3-IE3 132SX2

Electrical data			
Rated motor frequency	50Hz	60Hz	
Rated motor power	7,5	9,0	kW
Rated motor speed	2920	3504	RPM
Rated motor voltage	400 / 690	440 - 480	V
Rated motor torque	25		Nm
Rated motor current	13,65 / 7,92	14,89 - 13,65	A
Starting motor current	7,9		xIn
Starting motor torque	2,0		xMn
Brakedown motor torque	2,5		
Starting			D.O.L
Efficiency class	IE3		
Efficiency	90,10%		100% load
	90,90%		75% load
	90,90%		50% load
Power factor cosp	0,88		100% load

General data		
Frame size	132	mm
Mounting	B3,B5,B35	
Weight	67kg	
Casing material	Cast Iron	
Protection	IP	55
Insulation class	F	
Temp. Rise	80K	
Vibration	2,8mm/s	
Duty	S1	
Dir. Rotation	Both	
PTC	3 x 150°C	
RAL	7031	
Site Conditions		
Ambient temperature	from -20°C to +40°C	
Altitude above sea level	1000 m	

Mechanical data				
Noise level	79	dB(A)	Bearing DE side	6308 ZZ C3
Moment of inertia	0,029	kg/m ²	Bearing NDE side	6308 ZZ C3

Certification:

Extras:

Drawing made by	Date	sign.
Dennis Barrit	26-10-2020	

There may be differences between rating plate and calculated values