

## DATA SHEET FOR THREE-PHASE SQUIRREL-CAGE MOTOR

# Type: DM3-IE3 280M4

Electrical data			
Rated motor frequency	50Hz	60Hz	
Rated motor power	90,0	108,0	kW
Rated motor speed	1485	1782	RPM
Rated motor voltage	400 / 690	440 - 480	V
Rated motor torque	579		Nm
Rated motor current	155,1 / 89,9	169,2 - 155,1	A
Starting motor current	6,9		xIn
Starting motor torque	2,0		xMn
Brakedown motor torque	2,6		
Starting			D.O.L
Efficiency class	IE3		
Efficiency	95,20%		100% load
	95,40%		75% load
	94,90%		50% load
Power factor cosφ	0,88		100% load

General data		
Frame size	280	mm
Mounting	B3,B5,B35	
Weight	664kg	
Casing material	Cast Iron	
Protection	IP	55
Insulation class	F	
Temp. Rise	80K	
Vibration	2,8mm/s	
Duty	S1	
Dir. Rotation	Both	
PTC	3 x 150°C	
RAL	7031	
Site Conditions		
Ambient temperature	from -20°C to +40°C	
Altitude above sea level	1000 m	

Mechanical data				
Noise level	80	dB(A)	Bearing DE side	6317 C3
Moment of inertia	2,13	kg/m2	Bearing NDE side	6317 C3

**Certification:**

CE

**Extras:**

--

--

--

Drawing made by	Date	sign.
Dennis Barrit	26-10-2020	

There may be differences between rating plate and calculated values

